

ULTRAMAT 23 Continuous Gas Analyzer

Landfill and biogas monitoring

Multi-Component NDIR Gas Analyzer

Up to 4 gas components can be measured simultaneously including three IR active gases such as CH₄, CO₂, CO, NO, SO₂, and in addition can measure O₂ using an electrochemical cell.

Applications: Landfill gas monitoring, biomass digester sites for continuous measurement of (CH₄, CO₂), methane, carbon dioxide, and (O₂) oxygen in recovered gases from landfill and biogas sites.

Landfill sites recover large quantities of gas (methane, carbon dioxide, oxygen, nitrogen) along with other trace constituents. Methane as renewable energy is consumed as a fuel to generate electricity while also reducing the carbon footprint.

A gas fired generator in continuous operation consumes the recovered gas stream for fuel to produce the electricity and must be operated at optimum efficiency. In order to monitor the concentration of methane, carbon dioxide, and oxygen in the recovered gas stream an analyzer instrument is utilized. The methane concentration in the gas stream can vary and this measurement is critical to the generator control system so that adjustments to speed and air/fuel ratio set points can be updated in order to minimize emissions and optimize electricity generated. For these reasons it often is required and makes sense to monitor the gas in a continuous fashion and therefore an analyzer is needed that requires minimal operation and maintenance attention, and that it is reliable through long periods of unmanned plant operation. The Ultramat 23 continuous gas analyzer capable of (real-time) measuring up to (4) gas components at once is the right choice for the task at hand.



Ultramat 23 specification

- Zero -Ambient air for O₂ span and CO₂ and CH₄
- Span -Calibration standard gas mixture of CH₄, CO₂, in N₂ balance.
- Simple menu driven interface via HMI
- Per component 4-20ma outputs
- 8 freely programmable relay outputs
- 3 binary inputs
- RS-485 Serial communication port
- 100Vol% CH₄ 0-100Vol% CO₂
- 0-25Vol% O₂
- Repeatability: $\pm= 1\%$ of measuring range for (CH₄, CO₂)
 $\pm= 0.05\%$ for O₂
- Zero Drift: Negligible with AUTOCAL enabled.
< 2% of measuring range/week.
- Span Drift: Negligible with AUTOCAL enabled. <2% of measuring range/week.



For more information, contact:

Siemens Industry, Inc.
7101 Hollister Road
Houston, TX 77040
Email: saasales.industry@siemens.com
www.usa.siemens.com/processanalytics

Siemens Industry, Inc.
Industry Automation Division
3333 Old Milton Parkway
Alpharetta, GA 30005

1-800-964-4114
info.us@siemens.com

www.usa.siemens.com/processanalytics

Subject to change without prior notice
Order No.: PIAFL-00034-0610
Printed in USA
© 2010 Siemens Industry, Inc.

The information provided in this flyer contains merely general descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.

All product designations may be trademarks or product names of Siemens AG or supplier companies whose use by third parties for their own purposes could violate the rights of the owners.